


hoja de datos tècnicos: MONTA COLOUR LINE 7150

Stand: 05/2020



monta Colour Line 7150 is a self-adhesive tape with coloured adhesive, and an alternative to tape with coloured PVC film.

It is ideal for printing with optimum results, thanks to the smooth and glossy surface of its Smart-PVC carrier, and suitable for sealing medium heavy to heavy cardboard boxes.

APLICACIONES

- / Printed as bold and attractive advertising medium
- / Sealing medium heavy to heavy cardboard boxes
- / Marking and colour coding

PROPERTIES

- / Great for printing with brilliant results
- / Good tensile strenght & stability, low elongation
- / High immediate tack and adhesion on various surfaces
- / Smooth and low noise unwinding
- / Resistant to moisture, diluted acids and alkalies
- / Temperature resistance: from approx. -20°C to approx. +70°C short term (after application at room temperature)
- / Suitable for recycling

TECHNICAL DATA	METRIC		IMPERIAL	
Backing	Smart-PVC			
Adhesive	Natural Rubber			
Color	red, yellow, dark blue, green			
Tensile force	N/25mm N/cm	min. 100 min. 40.2	lb/in	min. 23
Thickness	mm	0.055	mil	2.2
Adhesive strength on metal	cN/25mm N/cm	350 1.4	oz/in	12.9
Core Diameter	mm	76	in	3

The values given are typical values, and do not constitute a specification. We recommend testing the suitability of the self-adhesive tape for the designated application or use.

hoja de datos tècnicos: MONTA COLOUR LINE 7150

PRODUCT FEATURES

La idoneidad del producto para las siguientes propiedades:

silencioso	***	Termoformable	-
Resistencia al desgarro	**	Resistente a ácidos y soluciones alcalinas	**
adhesión inicial / tack	***	Resistente a la humedad	**
adhesión (acero)	**	Alta Elongación	**
Para superficies lisas	**	removible	*
Para diferentes superficies	**	Resistente a los rayos UV y al envejecimiento	-
Para superficies difíciles	**	Apto para troquelado	-
fácil y suave a desenrollar	***	Rollos de Aplicación Manual	***
imprimible (**en directo *Primer-Release)	***	Rollos para embalaje automático	***
baja temperatura	**	Sellado de cajas (Peso del la caja)	***
alta temperatura	**		