


Scheda tecnica: MONTA BIOPACK 860

Stand: 11/2019

monta biopack[®] is a sustainable self-adhesive tape, that meets the requirements on disintegration (composting), biodegradation, ecotoxicity and material characteristics of EN 13432, ASTM D 6400-04, AS 4736 (2006) and ISO 17088 (2012): Examined and certified by TÜV Austria, awarded with „OK COMPOST INDUSTRIAL“ conformity mark.



APPLICAZIONI

- / Sealing biodegradable bags and films and other sustainable packaging types
- / Bundling flowers and garden waste
- / Permanent closure of medium heavy to heavy cardboard boxes
- / Suitable for manual application in various hand- and table dispensers as well as in automated packaging machines.

PROPERTIES

- / Proven sustainability: Certified conformity with „OK COMPOST INDUSTRIAL“ scheme by TÜV Austria: Meets EN 13432, ASTM D 6400-04, AS 4736 (2006) and ISO 17088 (2012)
- / Strong and robust backing material
- / Excellent immediate tack and adhesion on various surfaces
- / Low elongation
- / Hand tearable
- / Temperature resistant: from -30°C to +70°C short term (after application at room temperature)
- / Easy to unwind
- / Vegan

Scheda tecnica: MONTA BIOPACK 860

TECHNICAL DATA	METRIC		IMPERIAL	
Backing	PLA			
Adhesive	Natural Rubber			
Color	transparent			
Tensile force	N/25mm N/cm	min. 80 min. 32,2	lb/in	min. 18,4
Thickness	mm	0,047	mil	1,9
Adhesive strength on metal	cN/25mm N/cm	500 2	oz/in	18,4
Core Diameter	mm	76	in	3

The values given are typical values, and do not constitute a specification. We recommend testing the suitability of the self-adhesive tape for the designated application or use.

PRODUCT FEATURES

Più asterisco più marcata é la caratteristica del rispettivo prodotto:

Srotolamento silenzioso	***	Alte temperature	*
Carico di rottura	**	Resistente alla umidità	*
Tack	**	Rimovibile	*
Adesione (acciaio)	***	Resistente agli UV e all'invecchiamento	*
Superfici lisce	***	Indicato per fustellatura	*
Superfici diversi tipi	***	Rotoli manuali	***
Superfici difficili	***	Rotoli macchinabili	***
Facilità e omogeneità di srotolamento	***	Certificato OK COMPOST INDUSTRIAL	*
stampabile (**direttamente *Primer-Release)	***	Green line	*
Basse temperature	*	Carton sealing (Peso del cartone)	***